



CALDO TURBO 2000 TECH



Residential



Remote controller supplied



PERFORMANCE

MODEL	V at 50 Hz	W max	DIMENSIONS (cm)	WEIGHT (Kg)
CALDO TURBO 2000 TECH	220-240	2.000 W	68,3 x 41,2 x 18	4,4

FEATURES

- Convector heater using natural convection
- Electronic control and remote controller to manage the stand-by function and the ventilation level (3 settings: Eco 750W / Comfort 1250 W / Rapid 2000W)
- Antifreeze function
- Temperature regulation: 5~37°C
- Turbo function to direct the heat flow towards
- Programmable timer up to 15 hours
- Backlit display in blue which shows the selected functions and the ambient temperature
- Anti-tip switch
- Integrated side handles
- Body in painted steel
- Double insulated
- IP20 protection
- Heated area: 20 m²



CALDO TURBO / CALDO 2000



Residential



CALDO 2000



PERFORMANCE

MODEL	V at 50 Hz	W max	DIMENSIONS (cm)	WEIGHT (Kg)
CALDO 2000	220-240	220-240	58,7 x 42,3 x 19 x 8	3
CALDO TURBO 1000	220-240	1.000 W	58,7 x 42,3 x 19 x 8	3
CALDO TURBO 1500	220-240	1.500 W		3
CALDO TURBO 2000	220-240	2.000 W		3
CALDO TURBO 2000 TIMER	220-240	2.000 W		3

FEATURES

- Convector heater using natural convection
- Model CALDO TURBO provided with a frontal grille to direct the heat flow forward
- Adjustable ambient thermostat
- Antifreeze function
- Can be wall-mounted (wall installation kit supplied)
- Body in painted steel
- Double insulated
- IP20 protection
- Heated area: 20 m²

Range:

- CALDO 2000: one model including 3 heating levels: 750 / 1250 / 2000W
- CALDO Turbo: 3 models with 3 heat setting each: Caldo Turbo 1000: 350 / 650 / 1000W Caldo Turbo 1500: 500 / 1000 / 1500W Caldo Turbo 2000: 750 / 1250 / 2000W