

#### **Industrial**






### PERFORMANCE

V at 50 Hz	kW		A	DIMENSIONS	WEIGHT (Kg)
	MIN	MAX	MAX	EXPAII	(Ng)
230	1,63	3,3	14,3	250 X 250 X420	7,5
400	2,5	5	7,2	250 X 250 X420	8
	at 50 Hz	at 50 Hz MIN 230 1,63	at 50 Hz MIN MAX 230 1,63 3,3	at 50 Hz MIN MAX MAX 230 1,63 3,3 14,3	MIN         MAX         MAX           230         1,63         3,3         14,3         250 X 250 X 420

### **FEATURES**

- Heaters ideally suited for heating small and medium sized industrial premises
- Manufactured in rugged steel cabinet with strong safety insulated handles
- Encapsulated stainless steel heating elements that are extrainsulated from the cabinet
- Provided with safety thermostat which guards against overheating and ensures that fire hazard does not arise
- 2 models: 3,3 or 5 kW
- Provided with room thermostat to maintain the desired temperature
- Selectable heating effect , between ½ and 1/1 through the selector switch
- The 5 kW model is provided with a CEE plug of 16A, 5 poles, IP44 while the 3kW model is provided with a Schuko plug of 16A IP44.
- Supplied with wall mounting kit.









# **VOLCANO PRO**







## PERFORMANCE

MODEL	V at 50 Hz	kW		A	m³/h	DIMENSIONS Lxpxh	WEIGHT (Kg)
		MIN	MAX	MAX		· ·	. 3/
VOLCANO PRO 6000	400	3	6	10	1600	340 X 390 X 510	7
VOLCANO PRO 9000	400	4,5	9	13	1700	340 X 390 X 510	7,5
		3 4,5	6 9	10 13			

### **FEATURES**

- Heaters ideally suited for heating medium sized industrial premises
- 2 models: 6 or 9 kW
- Very compact and unique dimension for both models
- Housing in steel sheet
- Provided with delay start and delay stop functions, settable on the panel
- Provided with a cooling down post ventilation function (max 10 minutes)
- Provided with a CEE plug of 16A, 5 poles, IP44
- Supplied with wall mounting kit



